

- V-Care Label -

## Matte White BOPP76 FT/VC80N/WG62

### PHYSICAL CHARACTERISTICS

---

#### Facestock

A matte white BOPP film with special resin filler surface to provide excellent thermal transfer printability and tensile strength. Can be printed by normal lithographic ink, letterpress, screen, flexo and gravure using UV, solvent or water-based inks. Compatible with thermal transfer resin-based or resin/wax combination ribbons.

Caliper            ISO 534            : 75 µm

---

#### Adhesive

An odourless emulsion acrylic permanent adhesive, with excellent aging resistance. This adhesive is compliant to BgVV Recommendation XIV, EEC Directive 90/128 and US FDA 21 CFR 175.105 (Adhesive) for indirect food contact. It is suitable for use in food packaging and processing labeling.

Minimum Application Temperature        : 0°C  
Product Functional Service temperature : 0°C / +80°C

---

#### Liner

A super-calendered white glassine paper.

Basis weight    ISO 536            : 60 gsm  
Caliper            ISO 534            : 54 µm

---

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	12.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	6.0 N/25mm (20mins)
Total Product Caliper	ISO 534	147 µm

#### Shelf life

1 year when stored at 22°C and 50% RH