

# TECHNICAL INFORMATION PRELIMINARY



- V-Care Label -

## Gloss White BOPP60 TC/VC80G/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A bright gloss white, top-coated BOPP film. Can be printed by letterpress, screen, flexo and gravure, using UV or solvent-based inks.

Caliper ISO 534 : 58  $\mu\text{m}$

#### Adhesive

An odourless emulsion acrylic permanent adhesive, with excellent aging resistance. This adhesive is compliant to BgVV Recommendation XIV, EEC Directive 90/128 and US FDA 21 CFR 175.105 (Adhesive) for indirect food contact. It is suitable for use in food packaging and processing labeling.

Minimum Application Temperature : 0°C  
Product Functional Service temperature : 0°C / +80°C

#### Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm  
Caliper ISO 534 : 54  $\mu\text{m}$

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	12.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	6.0 N/25mm (20mins)
Total Product Caliper	ISO 534	130 $\mu\text{m}$

#### Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y01042013  
Rev00