

# TECHNICAL INFORMATION PRELIMINARY



## Super White Gloss/FT61N/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm  
Caliper ISO 534 : 88  $\mu$ m

#### Adhesive

An emulsion acrylic ultra-removable adhesive designed for superior removability on a wide variety of substrates. Features good initial tack. Meets US FDA indirect food contact requirements (21 CFR 175.105).

Minimum Application Temperature : +5°C  
Product Functional Service Temperature: -20°C / + 80°C

#### Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm  
Caliper ISO 534 : 54  $\mu$ m

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	1.2 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	1.0 N/25mm (20mins)
Total Product Caliper	ISO 534	146 $\mu$ m

#### Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y01042013  
Rev00