

TECHNICAL INFORMATION PRELIMINARY



- Car Window Label -

SWG80/MT01N/WG62

PHYSICAL CHARACTERISTICS

Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 88 μm

Adhesive

An emulsion acrylic removable adhesive, with excellent aging resistance. Specially designed for clean removal from car window shields.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -5°C / +65°C

Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 60 gsm
Caliper ISO 534 : 51 μm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	0.9 N/25mm (20mins)
Total Product Caliper	ISO 534	157 μm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y01042013
Rev00